

Reference

- [1] Şehovsov, G.A. (2009). *Sovremennyye geodezicheskie metody opredeleniya deformatsii inzhenernykh sooruzhenii* [Modern geodetic methods for determining the deformations of engineering structures]. N. Novgorod, NNGASU, 156. (in Russ).
- [2] Gerasimov V.A, Lobazov V.Я., Reznik B.E. (2010). *Konsepsiya geodezicheskogo monitoringa deformatsionnykh processov. Geoprofi* [The concept of geodetic monitoring of deformation processes], №1, 17-21. <https://doi.org/10.1088/0957-0233/25/10/105004>. 73.(in Russ).
- [3] Mustafin M.G., Valkov V.A., Kazantsev A.I. (2017). *Monitoring of deformation processes in buildings and structures in metropolises. Procedia Engineering*, Volume 189, 729-736. <https://doi.org/10.1016/j.proeng.2017.05.115>. (in Eng).
- [4] Zhang X. (2017). *Different monitoring methods for building deformation of practical exploration. Journal of Physics: Conf. Series* 910, 012029. <https://doi.org/10.1088/1742-6596/910/1/012029>. (in Eng).
- [5] Xu YL, Chen B, Ng CL, Wong KY, Chan WY. (2010). *Monitoring temperature effect on a long suspension bridge. Struct Control Health*, 17, 632-53. <https://doi.org/10.1002/stc.340>. (in Eng).
- [6] Okiemute E.S., Olujimi O.F. (2018). *Monitoring and analysis of vertical and horizontal deformations of a large structure using conventional geodetic techniques. Journal of Environment and Earth Science*, Vol.8, № 12,. 52-61. <https://doi.org/10.5281/zenodo.2529964>. (in Eng).
- [7] Baltiyeva A. A., Raskaliyaev A. S., Samsonenko A. I., Shamganova L. S., Fan H. (2020). *Development of the software and technical complex of the high-precision satellite positioning system in the conditions of open pit mining processes. Kompleksnoe Ispol'zovanie Mineral'nogo syr'â/Complex Use of Mineral Resources/Mineraldik Shikisattardy Keshendi Paidalanu*, 4 (315). P. 42-48. <https://doi.org/10.31643/2020/6445.35>. (in Eng).
- [8] Janicka J., Błaszczak-Bąk W., Rapinski J., Suchocki C. (2020). *Application of the msplit estimation method in the detection and dimensioning of the displacement of adjacent planes. Remote Sensing*, 12(19), 1-17. <https://doi.org/10.3390/rs12193203>. (in Eng).
- [9] Hayakawa Y., Kusumoto Sh., Matta N. (2016). *Application of terrestrial laser scanning for detection of ground surface deformation in small mud volcano. Hayakawa et al. Earth, Planets and Space*, 68:114. <https://doi.org/10.1186/s40623-016-0495-0>. (in Eng).
- [10] Lienhart W. (2017). *Geotechnical monitoring using total stations and laser scanners: critical aspects and solutions. Journal of Civil Structural Health Monitoring* volume 7, 315–324. <https://doi.org/10.1007/s13349-017-0228-5>. (in Eng).
- [11] Kovanič, L'; Blistan, P.; Urban, R.; Štroner, M.; Pukanská, K.; Bartoš, K.; Palková, J. (2020). *Analytical determination of geometric parameters of the rotary kiln by novel approach of TLS point cloud segmentation*, 10, 7652. (in Eng).
- [12] Yuwono B.D., Prasetyo Y. (2019). *Analysis deformation monitoring techniques using GNSS survey and terrestrial survey. IOP Conf. Series: Earth and Environmental Science*, 313, 012045. <https://doi.org/10.1088/1755-1315/313/1/012045>. (in Eng).
- [13] Sedlak V. (2015). *Some specific procedures in solving the deformation vector for mining undermined areas. Journal of materials and engineering structures*, 2, 99–110. (in Eng).
- [14] Jukov B.N., Karpik A.P. (2003). *Geodezicheskii kontrol inzhenernykh obektov promyslennykh predpriatii i grajdanskih kompleksov* [Geodetic control of engineering facilities of industrial enterprises and civil complexes]. Novosibirsk, SGGA, 356. <https://doi.org/10.5862/MCE.46.6>. (in Russ).
- [15] Luccio M. (2002). *The concrete and the clay: monitoring large structure deformation. GPS World*, Vol. 13, No. 8, 16. <https://doi.org/10.1016/j.proeng.2017.05.115>. (in Eng).